

Application No. : 10/780,350
Filed : February 16, 2004

IN THE CLAIMS

Please cancel Claims 62-86 without prejudice, and add new Claims 87-206 as follows:

1.-86. (Cancelled)

5 87. (new) A first computerized device configured to place a telephone call via a circuit switched telephone network to a second computerized device, comprising:

 a telephone subscriber interface adapted to be coupled to the circuit switched telephone network;

 a computer readable medium;

10 a set of digital circuits that includes a processor, wherein the set of digital circuits cooperatively function to:

 cause a set of telephone dialing digits to be coupled via the telephone subscriber interface to the circuit switched telephone network to cause a circuit-switched telephone call to be placed to the second computerized device, and a telephone ringing signal
15 indication to be delivered by the telephone network to the second computerized device, wherein a circuit-switched telephone connection is established to couple into communication the first and second computerized devices;

 cause a data segment to be sent from the first computerized device to the second computerized device via the established circuit-switched telephone connection, wherein
20 the data segment comprises information used to set up a packet switched data connection between the first and second computerized devices; and

 cause data to be communicated from the first computerized device to the second computerized device utilizing the packet switched data connection;

 wherein the packet switched data connection is established via a packet switched
25 transmission path that is different than a circuit-switched transmission path over which the circuit-switched telephone connection is established, and wherein at least one of the computerized devices is a user computerized device with a user interface, and the packet switched data connection is used to carry application layer data for presentation to a user via the user interface.

88. (new) The first computerized device of Claim 87, wherein the data segment comprises a set of tones automatically generated by the first computerized device, and wherein the tones are sent through the established circuit switched telephone connection.

89. (new) The first computerized device of Claim 87, wherein the data segment
5 comprises a set of touch tones entered by a user, and wherein the tones are transmitted through the circuit switched telephone connection.

90. (new) The first computerized device of Claim 87, further comprising a digital camera, and wherein the first computerized device is a smart telephone and the packet-switched data connection is used to transfer digital picture data captured by the digital camera.

10 91. (new) The first computerized device of Claim 87, further comprising a digital video camera, and wherein the first computerized device is a smart telephone and the packet-switched data connection is used to transfer digital video data captured by the digital video camera.

92. (new) The first computerized device of Claim 87, further comprising a user input
15 device and a graphical user interface, and wherein the first computerized device is a smart telephone and the packet-switched data connection is used to transfer real-time textual application sharing data.

93. (new) The first computerized device of Claim 87, wherein the telephone
20 subscriber interface comprises a voice channel of a wireless air interface, and both the circuit-switched telephone connection and the packet data connection are multiplexed for communication via the wireless air interface.

94. (new) The first computerized device of Claim 87, wherein the first computerized device implements a client-side application program communication protocol and the second computerized device implements a server-side application program communication protocol.

25 95. (new) The first computerized device of Claim 87, wherein the first computerized device implements a server-side application program communication protocol and the second computerized device implements a client-side application program communication protocol.

96. (new) The first computerized device of Claim 87, wherein the telephone subscriber interface comprises a voice channel of a wireless air interface, and both the circuit-

switched telephone connection and the packet data connection are multiplexed for communication via the wireless air interface.

97. (new) The first computerized device of Claim 87, wherein the data segment comprises a session layer address.

5 98. (new) The first computerized device of Claim 87, wherein the data segment comprises a transport layer address.

99. (new) The first computerized device of Claim 87, wherein the data segment comprises a network layer address.

10 100. (new) The first computerized device of Claim 87, wherein the data segment comprises an application layer address.

101. (new) The first computerized device of Claim 87, wherein the packet switched data connection comprises a TCP/IP stream socket established across the Internet.

102. (new) The first computerized device of Claim 87, wherein the data segment is a SYN segment in a TCP/IP connection setup sequence.

15 103. (new) The first computerized device of Claim 87, wherein the data segment is a SYN segment.

104. (new) The first computerized device of Claim 103, wherein the SYN segment comprises a packet switched network address defined in at least one protocol layer from the group consisting of the network layer, the transport layer, the session layer and the application layer.
20

105. (new) The first computerized device of Claim 87, wherein at least one of the first and second computerized devices is a smart telephone device.

106. (new) A second computerized device for use in a system where a first computerized device initiates a telephone call via a circuit switched telephone network to the second computerized device, comprising:
25

a telephone subscriber interface adapted to be coupled to the circuit switched telephone network;

a computer readable medium;

a set of digital circuits that includes a processor, wherein the set of digital circuits cooperatively function to:
30

detect at the telephone subscriber interface an incoming telephone call generated in response to a set of telephone dialing digits coupled by the first computerized device to the circuit switched telephone network, wherein the incoming telephone call includes a telephone ringing signal;

5 responsive to the detection, cause the telephone subscriber interface to be placed into an off-hook state to establish a circuit switched telephone connection with the first computerized device;

identify a data segment received at the telephone subscriber interface from the first computerized device via the established circuit switched telephone connection;

10 cause a packet switched data connection to be established with the first computerized device by using at least partially information contained in the data segment; and

cause application layer data to be communicated between the first and second computerized devices via the packet switched data connection;

15 wherein the packet switched data connection is established via a packet switched transmission path that is different than a circuit-switched transmission path over which the circuit-switched telephone connection is established, and wherein at least one of the first and second computerized devices is a user computerized device with a user interface, and the packet switched data connection is used to carry the application layer data for presentation to a user via
20 the user interface.

107. (new) The second computerized device of Claim 106, wherein the data segment comprises a set of tones automatically generated by the first computerized device, and wherein the tones are received by the second computerized device via the established circuit switched telephone connection.

25 108. (new) The second computerized device of Claim 106, wherein the data segment comprises a set of touch tones entered by a user at the first computerized device and the touch tones are received by the second computerized device via the circuit switched telephone connection.

109. (new) The second computerized device of Claim 106, further comprising a digital camera, and wherein the first computerized device is a smart telephone and the packet-switched data connection is used to transfer digital picture data captured by the digital camera.

110. (new) The second computerized device of Claim 106, further comprising a digital
5 video camera, and wherein the first computerized device is a smart telephone and the packet-switched data connection is used to transfer digital video data captured by the digital video camera.

111. (new) The second computerized device of Claim 106, further comprising a user input device and a graphical user interface, and wherein the first computerized device is a smart
10 telephone and the packet-switched data connection is used to transfer real-time textual application sharing data.

112. (new) The second computerized device of Claim 106, wherein the telephone subscriber interface comprises a voice channel of a wireless air interface, and wherein both the circuit-switched telephone connection and the packet data connection are multiplexed for
15 communication via the wireless air interface.

113. (new) The second computerized device of Claim 106, wherein the first computerized device implements a client-side application program communication protocol and the second computerized device implements a server-side application program communication protocol.

20 114. (new) The second computerized device of Claim 106, wherein the first computerized device implements a server-side application program communication protocol and the second computerized device implements a client-side application program communication protocol.

25 115. (new) The second computerized device of Claim 106, wherein the telephone subscriber interface comprises a voice channel of a wireless air interface, and wherein both the circuit-switched telephone connection and the packet data connection are multiplexed for communication via the wireless air interface.

116. (new) The second computerized device of Claim 106, wherein the data segment comprises a session layer address.

117. (new) The second computerized device of Claim 106, wherein the data segment comprises a transport layer address.

118. (new) The second computerized device of Claim 106, wherein the data segment comprises a network layer address.

5 119. (new) The second computerized device of Claim 106, wherein the data segment comprises an application layer address.

120. (new) The second computerized device of Claim 106, wherein the packet switched data connection comprises a TCP/IP stream socket established across the Internet.

10 121. (new) The second computerized device of Claim 106, wherein the data segment is a SYN segment in a TCP/IP connection setup sequence.

122. (new) The second computerized device of Claim 106, wherein the data segment is a SYN segment.

123. (new) The second computerized device of Claim 122, wherein the SYN segment comprises a packet switched network address defined in at least one protocol layer from the group consisting of the network layer, the transport layer, the session layer and the application layer.

124. (new) The second computerized device of Claim 106, wherein at least one of the first and second computerized devices is a smart telephone device.

20 125. (new) A computerized system comprising:
a computer readable medium;
a set of digital circuits that includes a processor, wherein the set of digital circuits cooperatively function to:

25 cause a set of telephone number dialing digits to be coupled at least indirectly to a public switched telephone network, wherein the set of telephone number dialing digits identify a recipient telephony subscriber endpoint device, and wherein the public switched telephone network is characterized in that it determines a route for an outgoing communication to follow in order for the outgoing communication to be delivered to the recipient telephony subscriber endpoint device based upon the telephone number dialing digits;

cause a data segment to be sent as a part of the outgoing communication to the recipient telephony subscriber endpoint device, wherein the data segment contains at least a packet switched network address that can be used by the recipient telephony subscriber endpoint device to establish the packet switched data connection, wherein once the packet switched data connection is established, the packet switched data connection is at least indirectly coupled to an application layer program in the recipient telephony subscriber endpoint device; and

cause a data packet to be sent the recipient telephony subscriber endpoint device via the packet switched data connection;

wherein the packet switched data connection is established via a packet switched transmission path that is different than the route followed by the outgoing communication through the public switched telephone network to the recipient telephony subscriber endpoint device based upon the set of telephone number dialing digits.

126. (new) The computerized system of Claim 125, wherein the packet switched data connection is a session layer packet switched data connection and the data packet sent to the application layer program is an unsolicited data packet.

127. (new) The computerized system of Claim 126, wherein the packet switched data connection uses an acknowledged packet protocol.

128. (new) The computerized system of Claim 127, wherein the packet switched data connection comprises a TCP/IP stream socket connection.

129. (new) The computerized system of Claim 125, wherein the data packet sent to the application layer program is an unsolicited data packet.

130. (new) The computerized system of Claim 125, wherein the computerized system further comprises a telephony interface which is used to couple information to the public switched telephone network.

131. (new) The computerized system of Claim 125, wherein the recipient telephony subscriber endpoint device is a recipient wireless subscriber device, the telephone number dialing digits correspond to the telephone number used to reach the recipient wireless subscriber device from the public switched telephone network, and the recipient wireless subscriber device is configured to receive both PSTN data packets and packet switched data packets via a

----- multiplexed wireless path that couples the recipient wireless subscriber device to a multiplexed wireless infrastructure side equipment that couples to both the public switched telephone network and a packet switched telephone network.

132. (new) The computerized system of Claim 131, wherein the data packet sent to the
5 recipient wireless subscriber device carries application layer data that is coupled to a user via a user interface provided by the recipient wireless subscriber device.

133. (new) The computerized system of Claim 125, wherein the outgoing communications path is a circuit switched voice band channel established in response to the recipient wireless subscriber device answering a telephone call.

10 134. (new) The computerized system of Claim 125, wherein the outgoing communications path is a PSTN datagram path that is routed based at least partially upon the telephone number dialing digits.

135. (new) The computerized system of Claim 125, wherein at least one of the functions of the set of digital circuits is triggered in response to a user input entered by a user into
15 a user input device.

136. (new) The computerized system of Claim 125, wherein at least one of the functions of the set of digital circuits is triggered in response to a user input entered by a user into a user input device in response to windowed information on a display device.

137. (new) The computerized system of Claim 125, wherein the data segment
20 comprises a network layer address.

138. (new) The computerized system of Claim 125, wherein the data segment comprises a transport layer address.

139. (new) The computerized system of Claim 125, wherein the data segment comprises a session layer address.

25 140. (new) The computerized system of Claim 125, wherein the data segment comprises an application layer address.

141. (new) The computerized system of Claim 125, wherein the data segment is a SYN segment.

142. (new) The computerized system of Claim 141, wherein the SYN segment
30 comprises the packet switched network address, and wherein the packet switched network

address is defined in at least one protocol layer from the group consisting of the network layer, the transport layer, the session layer and the application layer.

143. (new) The computerized system of Claim 125, wherein the packet switched data connection is used to implement a client-server communication protocol whereby a client sends a request which is responded to by a server, and wherein the computerized system comprises the server.

144. (new) The computerized system of Claim 125, wherein the packet switched data connection is used to push at least one unsolicited data packet to the recipient telephony subscriber endpoint device.

145. (new) The computerized system of Claim 125, wherein the packet switched data connection is used to push at least one unsolicited data packet to the recipient telephony subscriber endpoint device, and wherein the recipient telephony subscriber endpoint device is a wireless device that couples to an infrastructure side equipment via a multiplexed wireless signal path.

146. (new) The computerized system of Claim 125, wherein the computerized system comprises a server, and wherein the server makes outbound circuit switched voice band calls.

147. (new) The computerized system of Claim 125, wherein the computerized system comprises a server, and wherein the server causes outbound PSTN datagrams to be routed to their destinations.

148. (new) The computerized system of Claim 125, wherein the computerized system is a smart telephone device.

149. (new) The computerized system of Claim 125, wherein at least one of the computerized system and the recipient telephony subscriber endpoint device is a smart telephone device.

150. (new) The computerized system of Claim 125, wherein the recipient telephony subscriber endpoint device is a smart telephone device that is at least indirectly coupled to both the public switched telephone network and a packet switched network via a multiplexed subscriber line interface that comprises a voice telephony path and a DSL data path carried on a single subscriber telephone line.

151. (new) The computerized system of Claim 149, wherein the recipient telephony subscriber endpoint device is a wireless subscriber smart telephone device that is at least indirectly coupled to both the public switched telephone network and a packet switched network via a multiplexed subscriber wireless interface that provides multiplexed communication signal paths that respectively carry PSTN datagrams and data packets to be routed by the packet switched network, and the data packet sent to the recipient wireless subscriber device carries application layer data that is coupled to a user via a user interface provided by the recipient wireless subscriber device.

152. (new) The computerized system of Claim 151, wherein the wireless subscriber smart telephone device is coupled via a wireless LAN to a remote handset that is in local wireless communication with the wireless subscriber smart telephone, so that the remote handset can communicate with the packet switched network via the multiplexed subscriber wireless interface.

153. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively function to cause an unsolicited data packet to be pushed to the wireless subscriber smart telephone device via the packet switched data connection.

154. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively function to cause a digital picture to be sent to the wireless subscriber smart telephone device via the packet switched data connection.

155. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively function to cause at least one data packet containing digital video to be sent to the wireless subscriber smart telephone device via the packet switched data connection.

156. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively functions to cause an unsolicited data packet to be pushed to the wireless subscriber smart telephone device via the packet switched data connection, and wherein the computerized system comprises a server side computerized system.

157. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively functions to cause a digital picture to be sent to the wireless subscriber smart telephone device via the packet switched data connection, and wherein the computerized system comprises a server side computerized system.

158. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively functions to cause at least one data packet containing digital video to be sent to the wireless subscriber smart telephone device via the packet switched data connection, and wherein the computerized system comprises a server side computerized system.

5 159. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively functions to cause at least one data packet containing at least a portion of a voice mail message to be sent to the wireless subscriber smart telephone device via the packet switched data connection and wherein the computerized system comprises a server side computerized system.

10 160. (new) The computerized system of Claim 151, wherein the set of digital circuits further cooperatively functions to cause at least one data packet containing at least a portion of message stored in a multimedia messaging server to be sent to the wireless subscriber smart telephone device via the packet switched data connection, and wherein the computerized system comprises a server side computerized system.

15 161. (new) A wireless subscriber telephony endpoint device that provides both a telephony connectivity and a packet data service connectivity by wirelessly coupling via a multiplexed wireless subscriber interface communication path to at least one wireless network access point that couples to separate telephony and packet switched network switching infrastructures, the telephony switching infrastructure characterized in that it uses telephone
20 dialing digits to determine how information is to be routed to subscriber telephony endpoints and the packet switched network switching infrastructure characterized in that it supports at least network and transport communication protocol stack layers, wherein the packet switched network switching infrastructure uses packet header information associated with one or more of the protocol stack layers to determine how a packet is to be routed to its destination, the wireless
25 subscriber telephony endpoint device comprising:

a user interface capable of supporting user interactions;

a multiplexed wireless air interface adapted to communicate with the at least one wireless network access point, wherein the multiplexed wireless air interface supports both the telephony connectivity and the packet data service connectivity;

30 a computer readable medium;

a set of digital circuits that includes a processor, wherein the set of digital circuits cooperatively function to:

cause an incoming communication to be detected, wherein the incoming communication is directed to the wireless subscriber telephony endpoint device based upon a set of telephone number dialing digits designated at an initiating communications endpoint device, the telephone number dialing digits identify the wireless subscriber telephony endpoint device on a wireless telephony network, and the incoming communication is routed at least partially via a route through the telephony switching infrastructure;

cause the incoming communication to be evaluated for the presence of a data segment, wherein the data segment contains at least an indication of a network address;

cause the packet switched data connection to be established by using at least partially the indication the network address;

cause a data packet to be received via the packet switched data connection; and

cause at least a portion of the data packet to be coupled to an application layer program;

wherein the packet switched data connection is established via a packet switched transmission path through the packet switched network switching infrastructure, and wherein the packet switched transmission path is different than the route through the telephony switching infrastructure followed by the incoming communication to the wireless subscriber telephony endpoint device.

162. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the packet switched data connection is a session layer packet switched data connection and the data packet coupled to the application layer program is an unsolicited data packet.

163. (new) The wireless subscriber telephony endpoint device of Claim 162, wherein the packet switched data connection uses an acknowledged packet protocol.

164. (new) The wireless subscriber telephony endpoint device of Claim 163, wherein the packet switched data connection comprises a TCP/IP stream socket connection.

165. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the data packet coupled to the application layer program is an unsolicited data packet.

166. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the wireless subscriber telephony endpoint device further comprises a telephony interface which is used to couple information to the public switched telephone network.

167. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein
5 the wireless subscriber telephony endpoint device is a wireless subscriber smart telephone device adapted to receive both PSTN data packets and packet switched data packets via the multiplexed wireless subscriber interface communication path.

168. (new) The wireless subscriber telephony endpoint device of Claim 167, wherein the data packet carries application layer data to be coupled to a user via the user interface.

10 169. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the set of digital circuits further cooperatively function to establish a circuit switched voice band channel in response to the wireless subscriber telephony device answering an incoming telephone call, and an outgoing communication issued by the wireless subscriber telephony endpoint device is routed through a communications path that includes the circuit switched voice band channel.

15 170. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein an outbound communications path used to route an outgoing communication issued by the wireless subscriber telephony device through the public switched telephone network is a PSTN datagram path that is established based at least partially upon a second set of telephone number dialing digits identifying a callee.

20 171. (new) The wireless subscriber telephony endpoint device of Claim 161, further comprising a user input device, and wherein at least one of the functions of the set of digital circuits is triggered in response to a user input entered by a user into the user input device.

172. (new) The wireless subscriber telephony endpoint device of Claim 161, further comprising a user input device and a display device, and wherein at least one of the functions of
25 the set of digital circuits is triggered in response to a user input entered by a user into the user input device in response to windowed information presented on the display device.

173. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the data segment comprises a network layer address.

174. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein
30 the data segment comprises a transport layer address.

175. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the data segment comprises a session layer address.

176. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the data segment comprises an application layer address.

5 177. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the data segment is a SYN segment.

178. (new) The wireless subscriber telephony endpoint device of Claim 177, wherein the SYN segment includes a packet switched network address defined in at least one protocol layer from the group consisting of the network layer, the transport layer, the session layer and the application layer.

179. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the packet switched data connection is used to implement a client-server communication protocol whereby a client sends a request which is responded to by a server, and the initiating communications endpoint device comprises the server.

15 180. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the packet switched data connection is used to push at least one unsolicited data packet to the wireless subscriber telephony endpoint device.

181. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the packet switched data connection is used to pull at least one solicited data packet to the wireless subscriber telephony endpoint device.

182. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the initiating communications endpoint device comprises a server, and wherein the server makes outbound circuit switched voice band calls.

25 183. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the initiating communications endpoint device comprises a server, and wherein the server causes outbound PSTN datagrams to be routed to their destinations.

184. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the initiating communications endpoint device is a smart telephone device.

30 185. (new) The wireless subscriber telephony endpoint device Claim 161, wherein the wireless subscriber telephony endpoint device is a wireless subscriber smart telephone device.

186. (new) The wireless subscriber telephony endpoint device of Claim 185, wherein the wireless subscriber telephony endpoint device is coupled via a wireless LAN to a remote handset that is in local wireless communication with the wireless subscriber telephony endpoint device, so that the remote handset can communicate with a packet switched network via the multiplexed subscriber wireless interface communication path.

187. (new) The wireless subscriber telephony endpoint device of Claim 185, wherein the set of digital circuits further cooperatively function to:

cause to be processed an unsolicited data packet that was pushed to the wireless subscriber telephony endpoint device via the packet switched data connection.

188. (new) The wireless subscriber telephony endpoint device of Claim 185, wherein the set of digital circuits further cooperatively function to:

cause a digital picture to be received at the wireless subscriber telephony endpoint device via the packet switched data connection.

189. (new) The wireless subscriber telephony endpoint device of Claim 185, wherein the set of digital circuits further cooperatively function to:

cause at least one data packet containing digital video to be sent from the wireless subscriber telephony endpoint device via the packet switched data connection.

190. (new) The wireless subscriber telephony endpoint device of Claim 185, wherein the user interface enables World Wide Web (WWW) browsing.

191. (new) The wireless subscriber telephony endpoint device of Claim 185, further comprising a digital camera.

192. (new) The wireless subscriber telephony endpoint device of Claim 185, further comprising a digital video camera.

193. (new) The wireless subscriber telephony endpoint device of Claim 185, further comprising a digital scanner.

194. (new) The wireless subscriber telephony endpoint device of Claim 185, wherein the user interface comprises a graphical user interface that is configured to cause a screen to be popped for real-time multimedia communication with the initiating communication endpoint device.

195. (new) The wireless subscriber telephony endpoint device of Claim 185,

wherein the user interface comprises a graphical user interface that is configured to cause a screen to be popped for real-time multimedia communication with a peer communication endpoint.

196. (new) The wireless subscriber telephony endpoint device of Claim 185, further comprising an application sharing program that supports the transmission of a digital picture from a local application program to a remote peer application program in a real-time interactive multimedia communications session.

197. (new) The wireless subscriber telephony endpoint device of Claim 185, further comprising an application sharing program that supports the transmission of a digital video motion image from a local application program to a remote peer application program in a real-time interactive multimedia communications session.

198. (new) The wireless subscriber telephony endpoint device of Claim 196, wherein the application sharing program further is configured to support the transmission of textual key strokes received by a local application program to be transmitted to a remote peer application program for display in a window on a remote peer device.

199. (new) The wireless subscriber telephony endpoint device of Claim 161, further comprising an application sharing program that supports the transmission of textual key strokes received by a local application program via a real-time packet data communications session to a remote peer application program for real-time display in a window on a remote peer device.

200. (new) The wireless subscriber telephony endpoint device of Claim 199, wherein a list of system users who are currently connected to the system with active connections is maintained in a dynamic database operated by an infrastructure side computerized system.

201. (new) The wireless subscriber telephony endpoint device of Claim 200, wherein the respective local and remote peer applications pop a screen of information onto respective display screens of the wireless subscriber telephony endpoint device and the remote peer device, to enable respective users to interact in real time using key strokes and at least one multimedia data source.

202. (new) The wireless subscriber telephony endpoint device of Claim 161, further comprising a digital camera, and wherein the set of digital circuits additionally cooperatively function to cause the wireless subscriber telephony endpoint device to transfer digital picture data

captured by the digital camera via the packet switched data connection to a remote endpoint device.

203. (new) The wireless subscriber telephony endpoint device of Claim 161, further comprising a digital video camera, and wherein the set of digital circuits additionally cooperatively function to cause the wireless subscriber telephony endpoint device to transfer digital video data captured by the digital video camera via the packet switched data connection to a remote endpoint device.

204. (new) The wireless subscriber telephony endpoint device of Claim 161, further comprising a user input device, and wherein the user interface comprises a graphical user interface, and wherein the set of digital circuits further cooperatively function to cause the wireless subscriber telephony endpoint device to perform at least one of transmitting and receiving real-time textual application sharing data via the packet switched data connection.

205. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the set of digital circuits further cooperatively function to cause at least one data packet containing at least a portion of a voice mail message to be downloaded to the wireless subscriber telephony endpoint device via the packet switched data connection.

206. (new) The wireless subscriber telephony endpoint device of Claim 161, wherein the set of digital circuits further cooperatively function to cause at least one data packet containing at least a portion of message stored in a multimedia messaging server to be downloaded to the wireless subscriber telephony endpoint device via the packet switched data connection.